

**THIS DOCUMENT MUST BE READ AND SIGNED AT THE TIME OF  
ISSUANCE OF PERMIT!**

# OWNER/BUILDER

## **REROOF – RENAIL ROOF SHEATHING**

### **R803.2.3.1: Sheathing fastenings: Wood Structural.**

Panel sheathing shall be fastened to roof framing with 8D ring-shank nails at 6 inches on center at edges and 6 inches on center at intermediate framing. Ring-shank nails shall have the following minimum dimensions:

1. 0.113 inch nominal shank diameter;
2. Ring diameter of 0.012 over shank diameter;
3. 16 to 20 rings per inch;
4. 0.280 inch full round head diameter; and,
5. 2 inch nail length.

## **REQUIRED INSPECTIONS:**

### **Metal Roof (*Tear Off*)**

1. Deck Nailing
2. Underlayment
3. Flashing
4. Final

### **Metal Roof (*Re-Cover*)**

1. Purlins
2. Underlayment
3. Flashing
4. Final

### **Shingle (*Tear Off*)**

1. Deck Nailing
2. Underlayment & Flashing
3. Final

***Note: PHOTOS WILL NOT BE ACCEPTED IN LIEU OF INSPECTIONS!!!***

Signature of Homeowner: \_\_\_\_\_

Date: \_\_\_\_\_

# OWNER/BUILDER

**THIS DOCUMENT MUST BE READ AND SIGNED AT THE TIME OF  
ISSUANCE OF PERMIT!**